



# Weatherford®

## REAL RESULTS

### Thru-Tubing Gas-Lift Straddle Diverts Gas Lift Deeper in Wellbore, Revives, Enhances Productivity on Well Killed by Water Coning

#### Objectives

- Deepen the gas injection point in the wellbore to divert the existing gas-lift gas to a point deeper in the well than the liquid loading point.
- Selectively isolate the zone with access for the gas-lift mandrel and the column water.
- Inject gas through the casing annulus to unload the liquid through a concentric gas-lift mandrel integrated within the mechanical straddle packer bottomhole assembly (BHA).

#### Results

- Weatherford deployed a gas-lift straddle assembly consisting of two mechanical packers separated by 2,000 ft (609.6 m) of 2 3/8-in. tubing with an integrated concentric gas-lift mandrel.
- The upper WidePak™ packer was set 18 ft (5.4 m) above an opened sliding sleeve door (SSD). The lower compression-set CT packer was set 800 ft (243.8 m) above the top interval, at the point between the produced oil and the fluid, which hydrostatically killed the well.
- Gas was pumped into the casing annulus, through the open SSD, and into the straddle/tubing annulus.
- When the pressure had built up sufficiently to enable the comingled gas and coned water to enter the concentric gas-lift mandrel, the liquid was then circulated out of the tubing and up to the surface. To compensate for a weak formation pressure, the gas injection was continued even after all the liquid had been unloaded.
- The well began to flow the week after the operation with 78 BOPD (12.4 m³/day), a positive indication that the liquid was effectively unloaded with the gas-lift straddle assembly.

#### Value to Client

- Using Weatherford's gas-lift straddle assembly saved the operator a considerable amount of cost by preventing a workover or other alternative options to enhance the formation pressure, such as drilling an injection well nearby.
- The most recent well survey indicated the well is currently producing with the following data: tubing hanging pressure (THP) - 170 psi (1.17 MPa); casing hanger pressure (CHP) - 760 psi (5.24 MPa); gross rate - 106 BLPD (16.8 m³/day); net oil - 78 BOPD (12.4 m³/day).

Weatherford's Thru-Tubing Straddle is a one-trip mechanical straddle-packer system that incorporates a Weatherford 2.72-in. WidePak packer and a 2.72-in. CT compression-set packer. The installation of this system aided liquid unloading by diverting the gas-lift point to deeper in the well, using existing gas lift to revive and enhance productivity on a water-coned killed well that had low formation pressures with a liquid level below the lowest gas-lift mandrel.



#### Location

Offshore Balikpapan, Indonesia

#### Well Type

Offshore, oil producer

#### Tubing Size

3 1/2-in., 9.2 lb/ft (13.7 kg/m)

#### Tubing ID

2.92 in. (74.17 mm)

#### Deviation

53.65° at 2,874 ft (875 m)

#### Setting Depth (Measured Depth)

- Upper packer: 7,030 ft (2142 m)
- Lower packer: 9,136 ft (2784 m)

#### Products/Services

- Thru-Tubing Intervention
- WidePak packer (top packer)
- Concentric gas-lift mandrel
- CT packer (bottom packer)

Weatherford  
Matt Hall  
Region Business Unit Manager  
Thru Tubing  
matt.hall@ap.weatherford.com

Weatherford products and services are subject to the Company's standard terms and conditions, available on request or at weatherford.com. For more information contact an authorized Weatherford representative. Unless noted otherwise, trademarks and service marks herein are the property of Weatherford and may be registered in the United States and/or other countries. Weatherford products named herein may be protected by one or more U.S. and/or foreign patents. Specifications are subject to change without notice. Weatherford sells its products and services in accordance with the terms and conditions set forth in the applicable contract between Weatherford and the client.